

INTRINSIC OPTICAL FIBER TEMPERATURE AND STRAIN SENSOR FOR STRUCTURAL HEALTH MONITORING OF CONCRETE STRUCTURE

NUR AMIRA BINTI ZULKIFLLI

UNIVERSITI TEKNOLOGI MALAYSIA

INTRINSIC OPTICAL FIBER TEMPERATURE AND STRAIN SENSOR FOR
STRUCTURAL HEALTH MONITORING OF CONCRETE STRUCTURE

NUR AMIRA BINTI ZULKFLI

A project report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Engineering (Electronics and Telecommunications)

Faculty of Electrical Engineering
Universiti Teknologi Malaysia

JUNE 2018

In the name of Allah, the Most Merciful and the Most Beneficent

This thesis is dedicated to my mother and families. By their endless love, support, and prayers I have been blessed with position and higher education I have earned.

May Allah grant them a blessed and happy life on this earth and hereafter.

ACKNOWLEDGEMENT

First and foremost, I would to express my appreciation and gratitude to my supervisor Dr. Mohd Rashidi bin Salim for his continuous support and faith for me to complete my Master project, as well as for his guide, motivation, patience and enthusiasm. I have been blessed to have him as my supervisor, guided me and support my project with research grant for me complete my project. I also would like to take an opportunity to thank to Ir. Dr. Lim Kok Sing for providing me the item required for this project also for the chance to share his immense knowledge during the visit at Photonic Research Center, University of Malaya. Also to Dr. Asrul Izam bin Azmi, Dr Nor Akmal binti Fadil and Dr. Osayd M. Kharraz for countless guides in doing experimental work. Last but not least, to line of staff both from Faculty of Electrical Engineering (FKE) and Faculty of Mechanical Engineering (FKM) for their technical help and support.

Completing a higher education to master degree level was what my mother always encouraged. I want to take this chance to acknowledge my gratitude for everything she have done for me. There are no words to describe how much I feel blessed that I have nothing to offer to return her love and generosity.

ABSTRACT

Structure failure in civil engineering has been a motivation behind the development of monitoring system where it provides analytical data for evaluating the performance of building's structure, highway bridge, tunnel, etc., in order to minimize the risk of engineering disaster that would endanger public's safety and property. Fiber Optic Sensor (FOS) has been extensively studied and used since its first discoveries. However, erroneous in measurement due to cross-sensitivity of FBG is the main drawback for this sensing principle. Therefore, cascaded FBGs are developed to monitor temperature and strain. Another drawback of FBG toward temperature is it has poor thermal expansion properties. Thus, an analytical temperature model of FBG that able to enhance temperature sensitivity is developed and realized by coating the FBG with metal material that has good thermal expansion coefficient. The metal coating of FBG is done using electroless plating as this method is simpler and low cost.

ABSTRAK

Kegagalan struktur dalam kejuruteraan awam telah menjadi motivasi di sebalik pembangunan sistem pemantauan di mana ia menyediakan data analisis untuk menilai prestasi struktur bangunan, jambatan lebuhraya, terowong, dan sebagainya, untuk meminimumkan risiko bencana kejuruteraan yang akan membahayakan keselamatan awam dan harta benda awam. Sensor Fiber Optic (FOS) telah banyak dikaji dan digunakan sejak pertama kali ditemui. Walau bagaimanapun, salah pengukuran disebabkan oleh sensitiviti silang FBG adalah kelemahan utama untuk prinsip penderiaan ini. Oleh itu, FBGs dibangunkan untuk memantau suhu dan ketegangan. Satu lagi kelemahan FBG ke suhu adalah ia mempunyai ciri pengembangan haba rendah. Oleh itu, model suhu analitik FBG yang dapat meningkatkan kepekaan suhu dikaji dan direalisasikan dengan melapisi FBG dengan bahan logam yang mempunyai pekali pengembangan haba yang baik. Lapisan logam FBG dilakukan menggunakan penyaduran elektrolisis kerana kaedah ini adalah lebih mudah dan kosnya yang rendah,

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENT	iv
	ABSTRACT	v
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	x
	LIST OF FIGURES	xi
	LIST OF ABBREVIATIONS	xiii
	LIST OF SYMBOLS	xiv
1	INTRODUCTION	1
	1.1 Background of Study	1
	1.2 Problem Statement	2
	1.3 Motivation of the Study	3
	1.4 Objectives of Project	3
	1.5 Scope of Project	4
2	LITERATURE REVIEW	5
	2.1 Introduction	5
	2.2 Classification of Fiber Optic Sensor (FOS)	10
	2.2.1 Extrinsic FOS	10
	2.2.2 Intrinsic FOS	11
	2.3 Grating Fibers, Classification and Application	12

2.3.1	Fiber Bragg Grating (FBG)	13
2.3.2	Long Period Grating (LPG)	15
2.4	Cascaded Configuration of FOS	17
2.4.1	Single-Multi-Single (SMS) Mode Structure	17
2.4.2	FBG in SMS Structure	18
2.5	Metal Coated FBG	19
3	METHODOLOGY	21
3.1	Introduction	21
3.2	Theory and Analytical Model	21
3.2.1	FBG Characterization	22
3.2.2	Temperature Model of FBG	25
3.2.3	Strain Model of FBG	26
3.2.4	Temperature and Strain Model	28
3.3	Fabrication of FBG	28
3.4	Nickel-Coated FBG	30
3.4.1	Nickel Electroless Plating Process	30
3.4.2	Preparation of FBG	31
3.5	Cascaded FBG for Temperature and Strain Sensor	34
3.6	Experimental Setup	34
3.6.1	FBG Characterization	34
3.6.2	FBG Temperature Sensor	35
3.6.3	FBG Strain Sensor	36
3.6.4	Cascaded FBG for Temperature-strain Sensor	36
3.7	Research Planning and Schedule (Gantt Chart)	37
4	RESULTS AND DISCUSSIONS	40
4.1	Introduction	40
4.2	Analytical Temperature Model of FBG	40
4.3	Analytical Strain model of FBG	44
4.4	Experimental Finding	46
4.4.1	Bare FBG Temperature Sensor	46

4.4.2	Metallized FBG Sensor	52
4.4.3	Strain FBG Sensor	53
4.4.4	Temperature Compensation of FBG	56
5	CONCLUSIONS AND RECOMMENDATIONS	60
5.1	Conclusions	61
5.2	Recommendations	62
	REFERENCES	63

LIST OF TABLES

TABLE NO.	TITLE	PAGES
2.1	Summary of Case Study in Engineering Structure Failure	7
2.2	Review of Sensor Technologies and application in SHM	8
3.1	Nickel plating bath solution	33
3.2	Research planning and schedule (Gantt Chart) for Semester I	39
3.3	Research planning and schedule (Gantt Chart) for Semester II	40
4.1	Simulation Parameter on Optigrating	42
4.2	Temperature sensitivity respective to metal thermal expansion coefficient	44
4.3	Collected strain data from peak wavelength shift of Bragg wavelength over applied micro-strain applied	46
4.4	Characterization of FBGs at room temperature	47
4.5	Average Bragg wavelength shift of FBGs under temperature variances	50
4.6	Collected micro strain from experimental data and simulation data	56
4.7	Parameter of FBG1 and FBG2	57
4.8	Temperature compensation for FBG1 and FBG2	58

LIST OF FIGURES

FIGURE NO.	TITLE	PAGES
2.1	Extrinsic Fiber Optic Sensor	10
2.2	Extrinsic fabry perot interferometric (EPFI) sensor	11
2.3	Basic configuration of Evanescent U-shape sensor	11
2.4	Etched and non-etched part	12
2.5	Schematic grating period and reflection spectra of (a) uniform FBG and (b) CFBG	14
2.6	Sensing principle of TFBG	14
2.7	Sensing configuration of LPG	16
2.8	Corrugated LPG by chemical etching	16
2.9	SMS Structure	18
2.10	Experimental setup for writing FBG-in-SMS and on- line observing its transmission spectrum	18
2.11	Nickel disposition using electroless plating. (a) Axial cross section of Ni-Cu-coated fiber (b) Image of Ni- Cu coated FBG	20
2.12	Nickel disposition using electro plating. (a) Image of Ni-Cu coated FBG. (b) Radial cross section of Ni-Cu- coated fiber	20
3.1	2D XY plane view of refractive index (n) (b) 3D XY plane view of refractive index (n)	23
3.2	Physical structure of FBG and parameters	24
3.3	Reflectivity spectrum of FBG	24

3.4	Illustration of stress-strain in FBG	27
3.5	(a) Phase mask setup (b) adjusting the position of fiber on its platform for FBG writing	30
3.6	Phase mask	30
3.7	Preparation of FBG before nickel electroplating bath	34
3.8	Illustration of experimental setup for FBG characterization	36
3.9	Illustration of experimental setup for FBG temperature sensor	36
3.10	Illustration of experimental setup for FBG strain sensor	37
3.11	Illustration of experimental setup for strain FBG	38
4.1	Wavelength shift for metal-coated FBG and bare FBG	43
4.2	Curve fit graph of wavelength shift of normal FBG over strain variance	45
4.3	Reflection spectrum of FBG at (a) 1545 nm (b) 1547 nm	48
4.4	Transmission spectrum of FBG at (a) 1545 nm (b) 1547 nm	49
4.5	Development of spectra of FBGs under temperature variances at (a) 1545 nm (b) 1547 nm	51
4.6	Curve fitting graph for FBG (a) 1545 nm (b) 1547 nm	52
4.7	Nickel-coated FBG under microscope	53
4.8	Linearity of temperature sensitivity for Nickel coated FBG and Bare FBG	54
4.9	Development of FBG at 1561.14 nm (a) Transmission spectrum (b) Reflection spectrum	55
4.10	Comparison of measurement of wavelength shift between experimental and simulation (b) Curve fit graph	57
4.11	(a) Reflection (b) Transmission spectrum of cascaded FBG1 and FBG2	59

4.12	Development of reflection spectrum of cascaded fbg over strain variances	60
------	--	----

LIST OF ABBREVIATION

FOS	-	Fiber Optic Sensor
FBG	-	Fiber Bragg Grating
LPG	-	Long Period Grating
SHM	-	Structural Health Monitoring
AE	-	Acoustic Emission
MEMS	-	Micro Electromechanical System
RFID	-	Radio Frequency identification
EPFI		Extrinsic Fabry-perot interferometric
EDFA	-	Er-doped fiber amplifier
OSA	-	Optical Spectrum Analyzer
OTDR	-	Optical Time Domain Reflector
CFBG	-	Chirped Fiber Bragg Grating
TFBG	-	Tilted Fiber Bragg Grating
SMS	-	Single-Multi-Single
SMF	-	Single Mode Fiber
UV	-	Ultraviolet
RI	-	Refractive Index
FWHM	-	Full Width Half Maximum
ASE	-	Amplified Spontaneous Emission
SLSR	-	Sidelobe suppression ratio

LIST OF SYMBOLS

λ_{res}	-	Resonance wavelength
n_{co}	-	Core refractive index
n_{cl}^m	-	Refractive index of the effective m^{th} cladding mode
Λ	-	Grating period
λ	-	Wavelength of light
λ_{FWHM}	-	Wavelength of FWHM
λ_{B}	-	Bragg wavelength
S	-	Strength of reflection grating
N	-	Number of grating planes
L_{FBG}	-	Length of grating
η	-	Thermo-optic coefficient
α	-	Thermal expansion of silica
T	-	Temperature
n_{eff}	-	Effective refractive index
ρ_e	-	Photo-elastic coefficient
ε_z	-	Longitudinal strain

CHAPTER 1

INTRODUCTION

1.1 Background of the Study

In the field of civil engineering, fiber optic sensor (FOS) is widely used in early detection of structural failure such as a crack in a concrete structure. Crack on the concrete structure will develop due to thermal expansion and contraction when exposed to changes in temperature. Naturally, it will expand when the material is experiencing a hot temperature and contract when the temperature is colder. This crack development will lead to structural failure. FOS also has been used widely in another field such as biomedical, agriculture, chemical and automatic fire detection [1].

Features of FOS such as immune to the electromagnetic field, stable signal, robustness to a harsh environment and its compact size make this technology superior to other sensor technique. Fiber Bragg grating (FBG) is well known in its sensor application. It requires no calibration, length limit due to very small losses in optical fiber, passive technology, and long-term stability [2]. In this study, FBG, a type of grating-based FOS is used over another type of grating-based sensor configuration as FBG is simple inherent self-referencing capability, easily multiplexed and able to provide real-time monitoring.

1.2 Problem Statement

Recently, there are many engineering disasters has been reported. Some incident may have put many lives in stakes and has taken lives, such case like St. Francis dam where it broke and killed more than 432 sleeping residents [3]. Curing for concrete at its early age is a maintenance method in order to maintain adequate moisture and temperature in concrete to prevent cracking from developed. Which explain what happened to St. Francis dam where cracks were developed under the heat generated by the hydration of the cement. Furthermore, the heat generated by curing causes thermal stresses and of shrinkage of the mass concrete leading to further cracking and without early preventive action taken to cool down the concrete, this fateful event was allowed to take place.

Structural Health monitoring (SHM) application provides real-time inspection, monitoring, and damage detection and all together will provide an early warning to the responsible management to tackle the problem. Leakage in pipelines, tunnel sewerage leakage, cracks in the concrete structure, failing geotechnical infrastructure such as landslide can be monitored through a variety of techniques of fiber optic sensor (FOS) technique has been implemented.

Conventional techniques that are bulky, circuitry and electrical based possess many disadvantages such as prone to electromagnetic and electrical interference, hence the signal is not stable and also make them difficult to be implemented in a harsh environment. These drawbacks make FOS superior as it is immune to electrical and electromagnetic interference and its small in size makes this technology easy to be implemented and withstand in a harsh environment.

1.3 Motivation of the Study

In the field of civil engineering, there are many reported cases of engineering failure. There are few primary reasons for engineering disaster which are human factors, design flaws, material failure, extreme conditions or environments and most commonly and importantly the combination of these reasons. According to a research conducted by Swiss Federal Institute [4], a total of 800 cases of structural failure that killed 504 people, 594 people injured and total damage of million dollars.

The research concluded that the causes of structural failure were human errors in many aspects such as lack of knowledge, ignorant and carelessness, underestimation of influence, forgetfulness and relying upon others. Therefore, it is engineer duties to ensure the safety and durability of the project for the benefit of the company, civilian and workers. The aim of this research area is to develop FBG sensor that will provide real-time critical data for evaluating concrete performance derive from temperature and strain variances.

1.4 Objectives of the Study

This is study aim to develop dual FBG sensors, to measure strain optic coefficient and thermal sensitivity. Therefore, this study underlines the following key objectives:

1. To develop analytical temperature and strain model of FBG as sensor.
2. To determine the characteristic and capability of the proposed FBG sensor in response to the different temperature and strain variation at various wavelength shift.
3. To develop cascaded FBGs to overcome cross-sensitivity of FBG

1.5 Scope of the Study

In this paper, fundamental of FBG sensing principle, the behavior of metal coated FBG toward temperature and strain and preventive method for cross-sensitivity of FBG are discussed. The main goal of this paper is to develop a temperature model of FBG, aiming to enhance its temperature sensitivity which attributes to greater wavelength shift towards changes in temperature. This can be done by coating the FBG with metal material that has good thermal expansion coefficient.

This study is also conducted to overcome the main drawback of fiber Bragg grating which is cross-sensitivity as it may cause inaccurate judgment of interest parameter which is temperature and strain. This can be done by cascading two FBGs with two different center Bragg wavelengths with one FBG monitoring temperature while the other monitoring strain. Furthermore, a comparative experimental study is carried out between metal coated FBG and bare FBG in order to study the behavior of FBG after metallization.

REFERENCES

- [1] Zrelli, A., Bouyahi, M., & Ezzedine, T. (2016). Simultaneous monitoring of humidity and strain based on Bragg sensor. *Optik*, 127(18), 7326–7331.
- [2] S. Zheng, Long-period fiber grating moisture sensor with nanostructured coatings for structural health monitoring, *Struct. Health Monit.- An Int. J.* 14 (2) (2015) 148–157
- [3] Rogers, J.D. (2013) The 1928 St. Francis Dam failure and its impacts on American Civil Engineering. ASCE Press (web.mst.edu).
- [4] Florman, Samuel C. The Civilized Engineer. St. Martins Press, 1989.
- [5] Marzuki, Ahmad, et al. “Development of Landslide Early Warning System Using Macro-Bending Loss Based Optical Fibre Sensor.” *Journal of Physics: Conference Series*, vol. 622, 2015, p. 012059.
- [6] Tan, C.h., et al. “Fiber Bragg Grating Based Sensing System: Early Corrosion Detection for Structural Health Monitoring.” *Sensors and Actuators A: Physical*, vol. 246, 2016, pp. 123–128.
- [7] A. A. Khan, S. Zafar, N. Khan, and Z. Mehmood, “History, current status and challenges to structural health monitoring system aviation field,” *J. Space Technol.*, vol. 4, no. 1, pp. 67–74, 2014.
- [8] Shao, Li-Yang, et al. “Fiber Optic PH Sensor with Self-Assembled Polymer Multilayer Nanocoatings.” *Sensors*, vol. 13, no. 2, 2013, pp. 1425–1434.
- [9] Yehia, S., & Kashwani, G. (2013). Performance of Structures Exposed to Extreme High Temperature—An Overview. *Open Journal of Civil Engineering*, 3(3), 154–161.
- [10] Willam, K., Xi, Y., Lee, K., & Kim, B. (2009). Thermal Response of Reinforced Concrete Structures in Nuclear Power Plants. University of Colorado, Boulder, (2), 210.
- [11] Lichtenstein, A. G., “ The Siver Bridge Collapse Recounted”, *Journal of Performance of Constructed Facilities*, vol. 7, n4, Nov, 1993, pp. 249-261

- [12] Beitel, J., & Iwankiw, N. (2005). Historical Survey of Multi-Story Building Collapses Due to Fire. *Fire Protection Engineering*, 27
- [13] Conference, W., Engineering, E., August, C., & No, P. (2004). Lessons From Jan, 26, 2001 Gujrat (India) Earthquake, 444606(1874).
- [14] Rogers, L, Stambaugh, K, “Application of acoustic emission technology for health monitoring of ship structures”, Ship Structure Committee, Baltimore, Maryland, 2014
- [15] Michlmayr, G., Chalari, A., Clarke, A., & Or, D. (2017). Fiber-optic high-resolution acoustic emission (AE) monitoring of slope failure, (March 2016), 1139–1146.
- [16] S. Hewerdine. (n.d.). Use of Acoustic Emission in Inspection Investigations Wtthtn Tct. Icheme Symposium, (124).
- [17] Rippert, L., Papy, J. M., Wevers, M., & Van Huffel, S. (2002). Fibre optic sensor for continuous health monitoring in CFRP composite materials. *Smart Structures and Materials 2002: Modeling, Signal Processing, and Control*, t4693, 312–323.
- [18] Wiese, S., Jannsen, B., Jacob, A., & Kowalsky, W. (2000). Fiberoptical and Microwave Sensors for Health Monitoring in Concrete Structures. *Tu-Braunschweig.De*, 14–29.
- [19] Security, U. (n.d.). Microwave technology in alarm motion detection. Retrieved January 28, 2018, from <https://www.hkvstar.com/technology-news/microwave-technology-in-alarm-motion-detection.html>
- [20] Kim, J., Kwon, S., Park, S., & Kim, Y. (2013). A MEMS-based Commutation Module with Vibration Sensor for Wireless Sensor Network-based Tunnel-blasting Monitoring, 17, 1644–1653.
- [21] Ceylan, H., Gopalakrishnan, K., Kim, S., Taylor, P. C., Prokudin, M., & Buss, A. F. (2013). Highway Infrastructure Health Monitoring Using Micro- Electromechanical Sensors and Systems (MEMS). *Journal of Civil Engineering and Management*, 19(sup1), S188–S201.
- [22] Ikemoto, Y., Suzuki, S., Okamoto, H., Murakami, H., Lin, X., Itoh, H., & Asama, H. (2008). Force sensor system for structural health monitoring using passive RFID tags for structural health monitoring. *PORTABLE-POLYTRONIC 2008 – 2nd IEEE International Interdisciplinary Conference*
- [23] Fidanboyly, K.; Efendioglu, H.S. Fiber Optic Sensors and Their Applications. In *Proceedings of 5th International Advanced Technologies Symposium (IATS’09)*, Karabuk, Turkey, 13–15 May 2009.

- [24] Kang, J. U. (2013). *Fiber Optic Sensing and Imaging*. New York, NY: Springer New York. Pg. 39,102
- [25] Zhao, J. hai, Shi, Y. kai, Shan, N., & Yuan, X. qing. (2008). Stabilized fiber-optic extrinsic Fabry-Perot sensor system for acoustic emission measurement. *Optics and Laser Technology*, 40(6), 874–880.
- [26] Y. J. Rao, “Recent progress in fiber-optic extrinsic Fabry-Perot interferometric sensors,” *Opt. Fiber Technol.* 12, 227-237 (2006).
- [27] Zhao, Z., & Duan, Y. “A low cost fiber-optic humidity sensor based on silica sol-gel film”. *Sensors and Actuators, B: Chemical*, 160(1), 1340–1345 (2011).
- [28] Anguera, J., Anguera, J., Puente, C., Farrar, F. G., Sindoris, A., Hayes, S. T. Arabia, S. (2013). Strain Measurement Based On Sms Fiber Structure Sensor And, 55(11), 2576–2578.
- [29] Putha, K., Dantala, D., Kamineni, S., & Pachava, V. R. (2013). Etched optical fiber vibration sensor to monitor health condition of beam like structures. *Photonic Sensors*, 3(2), 124–130
- [30] Werneck, M. M., Allil, R. C. S. B., Ribeiro, B. A., & Nazaré, F. V. B. De. (2013). A Guide to Fiber Bragg Grating Sensors, 1–24. pg.2
- [31] Qi, J. (2013). A comparison study of the sensing characteristics of FBG and TFBG. *Sensor Review*, 33(1), 68–79.
- [32] Zhan, Y., Li, L., Yang, F., Gu, K., Wu, H., & Yu, M. (2013). An all-fibre multi-parameter sensor for composite structures based on a chirped fibre Bragg grating. *Opto-Electronics Review*, 21(3).
- [33] Liu, B. (2008), “Pure bending characteristic of tilted fiber Bragg grating”, *Journal of Electronic Science and Technology of China*, Vol. 6
- [34] Fu, M. (2007), “The improvement of the backward cladding core coupling in a tilted fiber grating by two acoustic flexural waves”, *Journal of Lightwave Technology*, Vol. 25, pp. 2751-6.
- [35] Liang, T. C., & Lin, Y. L. (2012). Ground vibrations detection with fiber optic sensor. *Optics Communications*, 285(9), 2363–2367.
- [36] Sehgal, P., & Dua, M. H. (2015). Designing of a Long Period Fiber Grating (LPFG) Using Optigrating Simulation Software, 2(6), 18–23.
- [37] James, Stephen W, and Ralph P Tatam. “Optical Fibre Long-Period Grating Sensors: Characteristics and Application.” *Measurement Science and Technology*, vol. 14, no. 5, 2003.

- [38] Wu, Q., Semenova, Y., Hatta, A. M., Wang, P., & Farrell, G. (2010). Single-Multiple-Single mode fiber structures for simultaneous measurement of strain and temperature. *Optical Sensing and Detection*.
- [39] Song, Dawei, et al. "A Simultaneous Strain and Temperature Sensing Module Based on FBG-in-SMS." *Measurement Science and Technology*, vol. 25, no. 5, 2014, p. 055205.
- [40] Y.-L. Li, H. Zhang, Y. Feng, and G. Peng, "A plating method for metal coating fiber Bragg grating," *Chin. Opt. Lett.*, vol. 7, pp. 115–117, 2009
- [41] Voorwald, H.j.c., et al. "Effects of Electroplated Zinc-Nickel Alloy Coatings on the Fatigue Strength of AISI 4340 High-Strength Steel." *Journal of Materials Engineering and Performance*, vol. 14, no. 2, Jan. 2005, pp. 249–257.
- [42] Y. L. Li, H. Zhang, Y. Feng, G. Peng, Metal coating of fiber Bragg grating and the temperature sensing character after metallization, *Opt. Fiber Technol.* 15 (4) (2009) 391–397
- [43] Feng, Yan, et al. "Temperature Sensing of Metal-Coated Fiber Bragg Grating." *IEEE/ASME Transactions on Mechatronics*, vol. 15, no. 4, 2010, pp. 511–519.
- [44] Devra, S., & Vikas, G. A. (2015). Fabrication and Applications of Fiber Bragg Grating-A Review. *Advanced Engineering Technology and Application*, 4(2), 15-25.
- [45] Werneck, M.M., Allil, R.C.S.B., Ribeiro, B.A., De Nazare, F.V.B., 2013. A guide to fiber bragg grating sensors. In: Cuadrado-Laborde, C. (Ed.), *Current Trends in Shortand Long-period Fiber Gratings*. InTech, pp. 1e24.
- [46] Dinesh Arora, Dr. Jai Prakash, Hardeep Singh & Dr.Amit Wason. "Reflectivity and Braggs Wavelength in FBG". *International Journal of Engineering (IJE)*, Vol. 5. Pages 341-349, 2011.
- [47] Wysokiński, Karol, et al. "New Methods of Enhancing the Thermal Durability of Silica Optical Fibers." *Materials*, vol. 7, no. 10, 2014, pp. 6947–6964.
- [48] Li, Yulong, et al. "Metal Coating of Fiber Bragg Grating and the Temperature Sensing Character after Metallization." *Optical Fiber Technology*, vol. 15, no. 4, 2009, pp. 391–397
- [49] Electroless. Nickel Plating: A Guide; Artistic Plating Company, Inc.: Milwaukee, WI, USA
- [50] Roark, Raymond J, Warren C. Young, and Richard G. Budynas. *Roark's Formulas for Stress and Strain*. New York: McGraw-Hill, 2002. Print.